

VENICE

STONE PLASTIC COMPOSITE

PRODUCT INFORMATION

Total Thickness (mm)	6.5mm
Core Thickness (mm)	5mm
Underlayment	1.5mm IXPE
Wear Layer (mm)	0.3mm/12mil
CE Certification	YES
Utilization Class	
Coating	PU Coating
Embossing	BP Surface
Bevelled	Painted Beveled
Fiberglass	No
Click	Unilin Push Lock System

PACK INFORMATION

Plank Size	7.16"x48.03" (182x1220mm)
Plank per Box	8
Sqft per Box	19.12sqft (1.7763m ²)
Pallet	70boxes

CERTIFICATE



TECHNICAL INFORMATION

Density	2000kg/m ³	
Dimensional Stability	X Direction: 0.05%	ISO 23999:2008
	Y Direction: -0.12%	
Castor Chair Resistance	No Delamination	EN425
Effect of castor chair	No visible damage	ISO 4918:2016
Residual indentation	0.01mm	ISO 24343-1:2007
STC Rating	73	
IIC Rating	72	
Impact Sound Insulation	70dB	ISO 717-2
Light Fastness	≥6	EN 20105-B02
Slip Resistance	R10	DIN 51130
Chemical Resistance	High Resistance	EN 423
Curling after exposure to heat	-0.09mm	ISO 23999:2008
Fire Resistance	Bfl-S1	EN ISO 9239-1
Stain Resistance	Index 0: Not affected	ISO 26987:2008
Antimicrobial activity	N/A	ASTM G 21-96
Wear Resistance	Group T	EN 660-2
Watertightness	N/A	EN13553
Water Resistance	100%	
Burning cigarette test	No visible change	EN 1399:1997 Method B
Migration of Certain Elements	Not Detected	"EN71-3:1994 + A 1:2000 + AC: 2002 "
CPSIA section 108 - Phthalates	Not Detected	CPSIC-CH- C1001-09.3